

3.4.5 Instruction Set Description

The instruction map is shown in [Figure 3-12](#) and the complete instruction set is summarized in [Table 3-17](#).

	000	040	080	0C0	100	140	180	1C0	200	240	280	2C0	300	340	380	3C0
0xxx																
4xxx																
8xxx																
Cxxx																
1xxx	RRC	RRC.B	SWPB		RRA	RRA.B	SXT		PUSH	PUSH.B	CALL		RETI			
14xx																
18xx																
1Cxx																
20xx									JNE/JNZ							
24xx									JEQ/JZ							
28xx									JNC							
2Cxx									JC							
30xx									JN							
34xx									JGE							
38xx									JL							
3Cxx									JMP							
4xxx									MOV, MOV.B							
5xxx									ADD, ADD.B							
6xxx									ADDC, ADDC.B							
7xxx									SUBC, SUBC.B							
8xxx									SUB, SUB.B							
9xxx									CMP, CMP.B							
Axxx									DADD, DADD.B							
Bxxx									BIT, BIT.B							
Cxxx									BIC, BIC.B							
Dxxx									BIS, BIS.B							
Exxx									XOR, XOR.B							
Fxxx									AND, AND.B							

Figure 3-12. Core Instruction Map

Table 3-17. MSP430 Instruction Set

Mnemonic	Description			V	N	Z	C
ADC (.B) ⁽¹⁾	dst	Add C to destination	dst + C → dst	*	*	*	*
ADD (.B)	src, dst	Add source to destination	src + dst → dst	*	*	*	*
ADDC (.B)	src, dst	Add source and C to destination	src + dst + C → dst	*	*	*	*
AND (.B)	src, dst	AND source and destination	src .and. dst → dst	0	*	*	*
BIC (.B)	src, dst	Clear bits in destination	not.src .and. dst → dst	-	-	-	-
BIS (.B)	src, dst	Set bits in destination	src .or. dst → dst	-	-	-	-
BIT (.B)	src, dst	Test bits in destination	src .and. dst	0	*	*	*
BR ⁽¹⁾	dst	Branch to destination	dst → PC	-	-	-	-
CALL	dst	Call destination	PC+2 → stack, dst → PC	-	-	-	-
CLR (.B) ⁽¹⁾	dst	Clear destination	0 → dst	-	-	-	-
CLRC ⁽¹⁾		Clear C	0 → C	-	-	-	0
CLRN ⁽¹⁾		Clear N	0 → N	-	0	-	-
CLRZ ⁽¹⁾		Clear Z	0 → Z	-	-	0	-
CMP (.B)	src, dst	Compare source and destination	dst - src	*	*	*	*
DADC (.B) ⁽¹⁾	dst	Add C decimaly to destination	dst + C → dst (decimally)	*	*	*	*
DADD (.B)	src, dst	Add source and C decimaly to dst	src + dst + C → dst (decimally)	*	*	*	*
DEC (.B) ⁽¹⁾	dst	Decrement destination	dst - 1 → dst	*	*	*	*

⁽¹⁾ Emulated Instruction

Table 3-17. MSP430 Instruction Set (continued)

Mnemonic	Description				V	N	Z	C
DECD (.B) ⁽¹⁾ dst	Double-decrement destination	dst - 2 → dst	*	*	*	*	*	*
DINT ⁽¹⁾	Disable interrupts	0 → GIE	-	-	-	-	-	-
EINT ⁽¹⁾	Enable interrupts	1 → GIE	-	-	-	-	-	-
INC (.B) ⁽¹⁾ dst	Increment destination	dst +1 → dst	*	*	*	*	*	*
INCD (.B) ⁽¹⁾ dst	Double-increment destination	dst+2 → dst	*	*	*	*	*	*
INV (.B) ⁽¹⁾ dst	Invert destination	.not.dst → dst	*	*	*	*	*	*
JC/JHS	label	Jump if C set/Jump if higher or same	-	-	-	-	-	-
JEQ/JZ	label	Jump if equal/Jump if Z set	-	-	-	-	-	-
JGE	label	Jump if greater or equal	-	-	-	-	-	-
JL	label	Jump if less	-	-	-	-	-	-
JMP	label	Jump	PC + 2 × offset → PC		-	-	-	-
JN	label	Jump if N set	-	-	-	-	-	-
JNC/JLO	label	Jump if C not set/Jump if lower	-	-	-	-	-	-
JNE/JNZ	label	Jump if not equal/Jump if Z not set	-	-	-	-	-	-
MOV (.B)	src, dst	Move source to destination	src → dst	-	-	-	-	-
NOP ⁽²⁾		No operation	-	-	-	-	-	-
POP (.B) ⁽²⁾	dst	Pop item from stack to destination	@SP → dst, SP+2 → SP	-	-	-	-	-
PUSH (.B)	src	Push source onto stack	SP - 2 → SP, src → @SP	-	-	-	-	-
RET ⁽²⁾		Return from subroutine	@SP → PC, SP + 2 → SP	-	-	-	-	-
RETI		Return from interrupt		*	*	*	*	*
RLA (.B) ⁽²⁾	dst	Rotate left arithmetically		*	*	*	*	*
RLC (.B) ⁽²⁾	dst	Rotate left through C		*	*	*	*	*
RRA (.B)	dst	Rotate right arithmetically		0	*	*	*	*
RRD (.B)	dst	Rotate right through C		*	*	*	*	*
SBC (.B) ⁽²⁾	dst	Subtract not(C) from destination	dst + 0FFFFh + C → dst	*	*	*	*	*
SETC ⁽²⁾		Set C	1 → C	-	-	-	-	1
SETN ⁽²⁾		Set N	1 → N	-	1	-	-	-
SETZ ⁽²⁾		Set Z	1 → Z	-	-	1	-	-
SUB (.B)	src, dst	Subtract source from destination	dst + .not.src + 1 → dst	*	*	*	*	*
SUBC (.B)	src, dst	Subtract source and not(C) from dst	dst + .not.src + C → dst	*	*	*	*	*
SWPB	dst	Swap bytes		-	-	-	-	-
SXT	dst	Extend sign		0	*	*	*	*
TST (.B) ⁽²⁾	dst	Test destination	dst + 0FFFFh + 1	0	*	*	*	1
XOR (.B)	src, dst	Exclusive OR source and destination	src .xor. dst → dst	*	*	*	*	*

(2) Emulated Instruction